

Johanson Design AB  
Anders Anderssons väg 7  
285 35 MARKARYD  
SWEDEN

## Testing of tables according to EN 15372:2016

(3 appendices)

<b>Customer:</b>	Johanson Design AB
<b>Test object/ID:</b>	Table/Dice
<b>Test method:</b>	EN 15372:2016 Furniture - Strength, durability and safety - Requirements for non-domestic tables. Test severity 2
<b>Scope:</b>	Complete test
<b>Date of test:</b>	2023-05-10 – 2023-05-18
<b>Test result:</b>	The tested object passed the test
<b>Reservation:</b>	The test results in this report apply solely to the specimen tested
<b>Test environment:</b>	23 ± 2°C and 50 ± 5% relative humidity
<b>Measurement uncertainty:</b>	Decision rule according to EN ISO IEC 17025:2018 clause 3.7 No account is taken of measurement uncertainty when reporting numerical results

### RISE Research Institutes of Sweden AB Department Building and Real Estate - Technical Wood Assessment

Performed by

Examined by



Annika Ahagen



Bengt-Åke Andersson

### Appendices

1. Test result (2 pages)
2. Test object (1 page)
3. Pictures (1 page)

### RISE Research Institutes of Sweden AB

Postal address  
Box 857  
501 15 BORÅS  
SWEDENOffice location  
Brinellgatan 4  
504 62 Borås  
SWEDENPhone / Fax / E-mail  
+46 10-516 50 00  
+46 33-13 55 02  
info@ri.se

This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Accred. No. 1002  
Testing  
ISO/IEC 17025

## Appendix 1

## Test result

Abbreviations: N/A = Not applicable  
N/T = Not tested

Table 1

1.	General requirements	EN 15372:2016	Results
1.1	<p>The table shall be designed to minimise the risk of injury to the user.</p> <p>All parts of the table with which the user comes into contact during intended use, shall be designed so that physical injury and damage are avoided.</p> <p>This requirement is met when:</p> <ul style="list-style-type: none"> <li>a. edges of tabletops which are directly in contact with the user are rounded or chamfered,</li> <li>b. all other edges accessible during intended use are free from burrs and/or sharp edges,</li> <li>c. ends of hollow components with a diameter greater than 7 mm and less than 12 mm where the accessible depth is greater than 10 mm, are closed or capped.</li> </ul> <p>Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.</p> <p>It shall not be possible for any load bearing part of the table to come loose unintentionally.</p> <p>All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use.</p>	5.1	Pass

Table 2

2.	Shear and squeeze points	EN 15372:2016	Results
2.1	<p>There shall be no shear and squeeze points created by parts of the table operated by powered mechanisms, i.e. springs, gas lifts and motorised systems.</p> <p>There shall be no shear and squeeze points created by forces applied during normal use.</p> <p><u>Note!</u> Shear and squeeze points that are created only during manually setting up and folding are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain.</p>	5.2	Pass

## Appendix 1

Table 3

3	Strength, durability	EN 1730:2012	Cycles	Load	Results
3.1	Horizontal static load test - Type 1 <sup>1</sup> - Type 2	6.2	10 10	400 N 200 N	N/A Pass
3.2	Vertical static load test on main surface	6.3.1	10	1250 N	Pass
3.3	Additional vertical static load test where the main surface has a length > 1 600 mm	6.3.2	10	1000 N	N/A
3.4	Vertical static load test on ancillary surface <sup>2</sup>	6.3.3	10	300 N	N/A
3.5	Horizontal durability test	6.4.1 6.4.2	15 000	300 N	Pass
3.6	Vertical durability test (For cantilever or pedestal tables)	6.5	15 000	300 N	N/A
3.7	Vertical impact test (for tables with glass in their construction) - Safety glass <sup>3</sup> - Other glass	6.6.1 6.6.2	10 10	180 mm 240 mm	N/A
3.8	Vertical impact test for all other tabletops	6.6.1 6.6.3	10	180 mm	Pass
3.9	Drop test <sup>4</sup> (for tables weighting more than 20 kg) Tables without glass (max 100 mm) Tables with glass (max 50 mm)	6.9	6 6		N/A
3.10	Stability under vertical load test <sup>5</sup> - Main surface (max 400 N) - Ancillary surface (max 200 N)	7.2	1 1	200 N	Pass N/A
3.11	Stability for tables with extension elements	7.3	1	200 N	N/A

<sup>1</sup> Type 1 tables have a main surface 600 mm or more above the floor surface and a surface area greater than 0.25 m<sup>2</sup>. All other tables are considered as Type 2.

<sup>2</sup> A table extension added in the centre of the table shall be considered as the main surface. A part of the main surface in the unextended configuration may become an ancillary surface in the extended configuration.

<sup>3</sup> Glass is considered to be safety glass if the glass fulfils the requirements in EN 12150-1:2012, Clause 8, fragmentation test; or where the mode of breakage ( $\beta$ ) according to EN 12600, is Type B or Type C.

<sup>4</sup> Determination of drop height are calculated according to table 1 in EN 1730:2012.

<sup>5</sup> Loads for stability tests are calculated according to table 2 in EN 1730:2012

## Appendix 2

**Test object**

Test object/ID: Table/Dice

**Dimensions <sup>1</sup>**

Length: 420 mm

Width: 420 mm

Height: 420 mm

Mass: 6.5 kg

**Components**

Frame/: Steel rod Ø8 mm  
Flexible foam, plywood 3 mm 4 mm 5 mm

Tabletop: Perforated metal sheet, 1.8 mm

Sampling: The test object was selected by the customer

Date of arrival at 2023-03-30

RISE test laboratory:

Observed defects before testing: No defects

<sup>1</sup> The dimensions are only intended to unambiguously identify the test object and do not claim to be metrologically accurate

## Appendix 3

## Pictures



Figure 1



Figure 2

# Verification

Transaction 09222115557493727571

## Document

**1196482B Johanson Design Dice EN 15372**

Main document

5 pages

*Initiated on 2023-05-30 11:16:32 CEST (+0200) by Bengt-Åke Andersson (BA)*

*Finalised on 2023-05-30 12:53:09 CEST (+0200)*

## Signing parties

**Bengt-Åke Andersson (BA)**

RISE Research Institutes of Sweden AB

Company reg. no. 556464-6874

*bengt-ake.andersson@ri.se*



*Signed 2023-05-30 11:16:52 CEST (+0200)*

**Annika Ahagen (AA)**

RISE Research Institutes of Sweden AB

Company reg. no. 556464-6874

*annika.ahagen@ri.se*



*Signed 2023-05-30 12:53:09 CEST (+0200)*

This verification was issued by Scrive. Information in italics has been safely verified by Scrive. For more information/evidence about this document see the concealed attachments. Use a PDF-reader such as Adobe Reader that can show concealed attachments to view the attachments. Please observe that if the document is printed, the integrity of such printed copy cannot be verified as per the below and that a basic print-out lacks the contents of the concealed attachments. The digital signature (electronic seal) ensures that the integrity of this document, including the concealed attachments, can be proven mathematically and independently of Scrive. For your convenience Scrive also provides a service that enables you to automatically verify the document's integrity at: <https://scrive.com/verify>

