

Johanson Design AB
Anders Anderssons väg 7
285 35 MARKARYD
SWEDEN

Testing of Flow easy chair with swivel base

(1 appendix)

Summary

Flow easy chair with swivel base meet the requirements for strength and security according to EN 16139:2013, level 1.

1 Introduction

On behalf of Johanson Design AB, a Flow easy chair with swivel base has been tested at SP in accordance with EN 16139:2013 Furniture - Strength, durability and safety - Requirements for non-domestic seating, level 1.

2 Test specimen



Figure 1 Flow easy chair with swivel base

Dimension: W=870 mm, D=940 mm, H=815 mm
Seat height: 420 mm
Frame/Foot: Foot in steel, Ø 735 mm. Pillar in steel, Ø 55 mm
Seat/Back rest: In moulded and laminated veneer with upholstery
Functions: Swivelling
Other info: -

The test specimen was selected by the customer and arrived at SP 2014-03-19.

SP Technical Research Institute of Sweden

Postal address
SP
Box 857
SE-501 15 BORÅS
Sweden

Office location
Västeråsen
Brinellgatan 4
SE-504 62 BORÅS

Phone / Fax / E-mail
+46 10 516 50 00
+46 33 13 55 02
info@sp.se

Laboratories are accredited by the Swedish Board for Accreditation and Conformity Assessment (SWEDAC) under the terms of Swedish legislation. This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

3 Test methods and test procedure

The test was carried out according to EN 16139:2013 Furniture – Strength, durability and safety – Requirements for non-domestic seating, level 1 and EN 1022:2005 Domestic furniture – Seating – Determination of stability.

The test was carried out in a climate of 23±2°C and 50 ±5% relative humidity.

The test methods are explained in table 1 – 3.

The test was carried out 2014-04-17 – 2014-05-12.

4 Results

Table 1

1.	General requirements	EN 16139	Req. fulfilled
1.1	Accessible corners shall be rounded or chamfered.	4.1	Passed
1.2	Edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair shall be rounded or chamfered.	4.1	Passed
1.3	Edges of handles shall be rounded or chamfered in the direction of the force applied.	4.1	N/A
1.4	All other edges shall be free from burrs and rounded or chamfered.	4.1	Passed
1.5	Ends of hollow components shall be closed or capped.	4.1	Passed
1.6	Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.	4.1	Passed
1.7	It shall not be possible for any load bearing part of the seating to come loose unintentionally.	4.1	Passed
1.8	All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use.	4.1	N/A
1.9	No shear and squeeze points when setting up and folding.	4.2.1	N/A
1.10	No shear and squeeze points under influence of powered mechanism.	4.2.2	N/A
1.11	No shear and squeeze points during use.	4.2.3	Passed

Table 2

2.	Stability	EN 1022	Req. fulfilled
2.1	Forwards overbalancing.	6.2	Passed
2.2	Forwards overturning for seating with footrest.	6.3	N/A
2.3	Sideways overbalancing, all seating without arms.	6.4	Passed
2.4	Sideways overbalancing, all seating with arms.	6.5	N/A
2.5	Rearwards overbalancing, all seating with backs.	6.6	Passed

Table 3

3.	Strength, durability	Reference EN 1728	Cycles	EN 16139 level 1	Req. fulfilled
3.1	Seat and back static load test.	6.4	10	Seat: 1600 N Back: 560 N	Passed
3.2	Seat front edge static load test.	6.5	10	1300 N	Passed
3.3	Vertical static load on back rests.	6.6	10	600 N Seat: 1300 N	Passed
3.4	Foot rest and leg rest static load test.	6.8 and 6.9	10	1300 N	N/A
3.5	Arm sideways static load test.	6.10	10	400 N	N/A
3.6	Arm downwards static load test.	6.11	5	750 N	N/A
3.7	Vertical upwards static load on arm rests.	6.13.1 and 6.13.2	10	250 N	N/A
3.8	Seat and back durability test.	6.17	100 000	Seat: 1000N Back: 300 N	Passed
3.9	Seat front edge durability test.	6.18	50 000	800 N	Passed
3.10	Arm durability test.	6.20	30 000	400 N	N/A
3.11	Foot rest durability test.	6.21	50 000	1000 N	N/A
3.12	Leg forward static load test.	6.15	10	500N Seat: 1000 N	Passed
3.13	Leg sideways static load test.	6.16	10	400 N Seat: 1000 N	Passed
3.14	Seat impact test.	6.24	10	240 mm	Passed
3.15	Back impact test.	6.25	10	210/38 mm/°	Passed
3.16	Arm impact test.	6.26	10	210/38 mm/°	N/A
3.17	Drop test (multiple seating).	6.27.1	2x5		N/A
3.18	Auxiliary writing surface static load test.	6.14	10	300 N	N/A
3.19	Auxiliary writing surface durability test.	6.22	10 000	150 N	N/A

5 Conclusion

At the end of the test, the tested piece did not exhibit any faults, fractures or other damage judged to affect its safety and functions when used in accordance with EN 16139:2013 level 1.

The test results apply solely to the specimen tested.

SP Technical Research Institute of Sweden Wood Technology

Performed by

Examined by

Jonas Hafmar

Bengt-Åke Andersson

Appendix

1. Pictures (1 page)

Appendix 1

Pictures



Figure 1 Flow easy chair with swivel base, view underneath