

Johanson Design AB  
Anders Anderssons väg 7  
285 35 MARKARYD  
SWEDEN

## Testing of seating furniture according to EN 16139:2013 (3 appendices)

<b>Customer:</b>	Johnson Design AB
<b>Test object/ID:</b>	Chair/Haddoc Conference
<b>Test method:</b>	EN 16139:2013 Furniture - Strength, durability and safety - Requirements for non-domestic seating. Test level 1
<b>Scope:</b>	Complete test
<b>Date of test:</b>	2016-06-09 – 2016-07-04
<b>Test result:</b>	The tested object passed the test
<b>Reservation:</b>	The test results in this report apply only to the particular Equipment Under Test (EUT)
<b>Test environment:</b>	23 ± 2°C and 50 ± 5% relative humidity
<b>Additional information:</b>	-

### SP Technical Research Institute of Sweden Sustainable Built Environment - Wood Technological Assessment

Performed by

Examined by

Michael Lindblad

Bengt-Åke Andersson

### Appendices

1. Test result (3 pages)
2. Description of test object (1 page)
3. Pictures (1 page)

---

#### SP Technical Research Institute of Sweden

Postal address  
SP  
Box 857  
SE-501 15 BORÅS  
Sweden

Office location  
Brinellgatan 4  
SE-504 62 BORÅS

Phone / Fax / E-mail  
+46 10 516 50 00  
+46 33 13 55 02  
info@sp.se

Laboratories are accredited by the Swedish Board for Accreditation and Conformity Assessment (SWEDAC) under the terms of Swedish legislation. This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

## Appendix 1

### Test result

Abbreviations: N/A = Not applicable  
N/T = Not tested

**Table 1**

1.	Safety	EN 16139	Result
1.1	<p><u>General requirements</u></p> <p>The seating shall be so designed as to minimise the risk of injury to the user.</p> <p>All accessible parts shall be so designed that physical injury and damage are avoided.</p> <p>This requirement is met when:</p> <ul style="list-style-type: none"> <li>a) accessible corners are rounded or chamfered;</li> <li>b) the edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded or chamfered;</li> <li>c) the edges of handles are rounded or chamfered in the direction of the force applied;</li> <li>d) all other edges are free from burrs and rounded or chamfered;</li> <li>e) the ends of hollow components are closed or capped.</li> </ul> <p>Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.</p> <p>It shall not be possible for any load bearing part of the seating to come loose unintentionally.</p> <p>All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use</p>	4.1	Pass
1.2	<p><u>Shear and squeeze points</u></p> <p>With the exception of tipping seats there shall be no shear and squeeze points created by parts of the seating operated by powered mechanisms, e.g. springs and gas lifts.</p> <p>There shall be no shear and squeeze points created by forces applied during normal use as well as during normal movements and actions</p> <p>Note!</p> <p>Shear and squeeze points that are created only during manually setting up and folding are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain.</p>	4.2	Pass
1.3	<p><u>Rolling resistance of the unloaded chair</u></p> <p>≥ 12 N when tested in accordance with EN 1335-3:2009, 7.4; and all castors are of the same type</p>	4.4	N/A

## Appendix 1

**Table 2**

<b>2.</b>	<b>Stability</b>	<b>EN 1335-3</b>	<b>Result</b>
2.1	Front edge overturning	7.1.1	Pass
2.2	Forwards overturning	7.1.2	Pass
2.3	Forwards overturning for chairs with footrest	7.1.3	N/A
2.4	Sideways overturning for chairs without arm rests	7.1.4	Pass
2.5	Sideways overturning for chairs with arm rests	7.1.5	N/A
2.6	Rearwards overturning	7.1.6	Pass
2.7	Rearwards overturning for chairs with adjustable back rest inclination	7.1.7	N/A

**Table 3**

<b>3.</b>	<b>Strength, durability</b>	<b>Reference EN 1728</b>	<b>Cycles</b>	<b>EN 16139 level 1</b>	<b>Result</b>
3.1	Seat and back static load test	6.4	10	Seat: 1600 N Back: 560 N	Pass
3.2	Seat front edge static load test	6.5	10	1300 N	Pass
3.3	Vertical static load on back rests	6.6	10	600 N Seat: 1300 N	Pass
3.4	Foot rest and leg rest static load test	6.8 and 6.9	10	1300 N	N/A
3.5	Arm sideways static load test	6.10	10	400 N	N/A
3.6	Arm downwards static load test	6.11	5	750 N	N/A
3.7	Vertical upwards static load on arm rests for stackable seating	6.13.2	10	250 N	N/A
3.8	Vertical upwards static load on arm rests for seating which may be moved when occupied	6.13.1	10	1200 N	N/A

## Appendix 1

3.	Strength, durability	Reference EN 1728	Cycles	EN 16139 level 1	Result
3.9	Seat and back durability test	6.17	100 000	Seat: 1000N Back: 300 N	Pass
3.10	Seat front edge durability test	6.18	50 000	800 N	Pass
3.11	Arm durability test	6.20	30 000	400 N	N/A
3.12	Foot rest durability test	6.21	50 000	1000 N	N/A
3.13	Leg forward static load test	6.15	10	500 N Seat: 1000 N	Pass
3.14	Leg sideways static load test	6.16	10	400 N Seat: 1000 N	Pass
3.15	Seat impact test	6.24	10x2	240 mm	Pass
3.16	Back impact test	6.25	10	210 mm/38°	Pass
3.17	Arm impact test	6.26	10	210 mm/38°	N/A
3.18	Auxiliary writing surface static load test	6.14	10	300 N	N/A
3.19	Auxiliary writing surface durability test	6.22	10 000	150 N	N/A

## Appendix 2

**Description of test Object**

Test object/ID: Armchair/Haddoc Conference

**Dimensions**

Width: 520 mm

Depth: 570 mm

Height: 725 mm

Seat height: 355 mm

Mass: 7.9 kg

**Components**

Column/legs Metal Ø 60 mm/Five arms stand

Seat shell: Plywood 10 mm

Footrest: -

Castors: -

Upholstery: -

Sampling: The test object was selected by the customer

Date of arrival at 2016-05-02

SP test laboratory:

Observed defects before testing: No defects

## Appendix 3

### Pictures



**Figure 1**



**Figure 2**



**Figure 3**



**Figure 4**