

Johanson Design AB
Anders Anderssons väg 7
285 35 MARKARYD
SWEDEN

Testing of seating furniture according to EN 16139:2013

(3 appendices)

| | |
|---------------------------------|--|
| Customer: | Johanson Design AB |
| Test object/ID: | Armchair/Plateau, 1-seater with armrest |
| Test method: | EN 16139:2013 Furniture - Strength, durability and safety - Requirements for non-domestic seating. Test level 1 |
| Scope: | Complete test |
| Date of test: | 2021-06-16 – 2021-07-15 |
| Test result: | The tested object passed the test |
| Reservation: | The test results in this report apply solely to the specimen tested |
| Test environment: | 23 ± 2°C and 50 ± 5% relative humidity |
| Measurement uncertainty: | Decision rule according to EN ISO IEC 17025:2018 clause 3.7 No account is taken of measurement uncertainty when reporting numerical results |

RISE Research Institutes of Sweden AB

Department Building and Real Estate - Technical Wood Assessment

Performed by

Examined by



Annika Ahagen



Bengt-Åke Andersson

Appendices

1. Test result (3 pages)
2. Test object (1 page)
3. Pictures (3 pages)

RISE Research Institutes of Sweden AB

Postal address

Box 857
501 15 BORÅS
SWEDEN

Office location

Brinellgatan 4
504 62 Borås
SWEDEN

Phone / Fax / E-mail

+46 10-516 50 00
+46 33-13 55 02
info@ri.se

This report may not be reproduced other than in full, except
with the prior written approval of the issuing laboratory.



Accred. No. 1002
Testing
ISO/IEC 17025

Appendix 1

Test result

Abbreviations: N/A = Not applicable
N/T = Not tested

Table 1

| 1. | Safety | EN 16139 | Result |
|-----|---|-------------|--------|
| 1.1 | <p><u>General requirements</u></p> <p>The seating shall be so designed as to minimise the risk of injury to the user.</p> <p>All accessible parts shall be so designed that physical injury and damage are avoided.</p> <p>This requirement is met when:</p> <ul style="list-style-type: none"> a) accessible corners are rounded or chamfered; b) the edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded or chamfered; c) the edges of handles are rounded or chamfered in the direction of the force applied; d) all other edges are free from burrs and rounded or chamfered; e) the ends of hollow components are closed or capped. <p>Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.</p> <p>It shall not be possible for any load bearing part of the seating to come loose unintentionally.</p> <p>All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use</p> | 4.1 | Pass |
| 1.2 | <p><u>Shear and squeeze points</u></p> <p>With the exception of tipping seats there shall be no shear and squeeze points created by parts of the seating operated by powered mechanisms, e.g. springs and gas lifts.</p> <p>There shall be no shear and squeeze points created by forces applied during normal use as well as during normal movements and actions</p> <p>Note!</p> <p>Shear and squeeze points that are created only during manually setting up and folding are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain.</p> | 4.2 | Pass |

Appendix 1

Table 2

| 2. | Stability | EN 1022:2018 | Result |
|-----|---|--------------|--------|
| 2.1 | Forwards overbalancing Requirement ≥ 20 N | 7.3.1 | Pass |
| 2.2 | Forwards overturning for seating with footrest | 7.3.2 | N/A |
| 2.3 | Corner stability test Requirement 30 kg | 7.3.3 | Pass |
| 2.4 | Sideways overbalancing, all seating without arms Requirement ≥ 20 N | 7.3.4 | Pass |
| 2.5 | Sideways overbalancing, all seating with arms Requirement ≥ 20 N | 7.3.5.2 | Pass |
| 2.6 | Sideways overbalancing, seating with raised side edges | 7.3.5.3 | N/A |
| 2.7 | Rearwards overbalancing, all seating with backs Requirement ≥ 196 N | 7.3.6 | Pass |

Table 3

| 3. | Strength, durability | Reference EN 1728 | Cycles | EN 16139 level 1 | Result |
|----------------|--|----------------------|--------|-----------------------------|--------|
| 3.1 | Seat and back static load test | 6.4 | 10 | Seat: 1600 N Back: 560 N | Pass |
| 3.2 | Seat front edge static load test | 6.5 | 10 | 1300 N | Pass |
| 3.3 | Vertical static load on back rests | 6.6 | 10 | 600 N Seat: 1300 N | Pass |
| 3.4 | Foot rest and leg rest static load test | 6.8 and 6.9 | 10 | 1300 N | N/A |
| 3.5 | Arm sideways static load test | 6.10 | 10 | 400 N | Pass |
| 3.6 | Arm downwards static load test | 6.11 | 5 | 750 N | Pass |
| 3.7 | Vertical upwards static load on arm rests for stackable seating | 6.13.2 | 10 | 250 N | N/A |
| 3.7 Annex B | Vertical upwards static load on arm rests for seating which may be moved when occupied | 6.13.1 | 10 | 1200 N | N/A |

Appendix 1

| 3. | Strength, durability | Reference EN 1728 | Cycles | EN 16139 level 1 | Result |
|------|---|----------------------|---------|----------------------------|--------|
| 3.8 | Seat and back durability test | 6.17 | 100 000 | Seat: 1000N Back: 300 N | Pass |
| 3.9 | Seat front edge durability test | 6.18 | 50 000 | 800 N | Pass |
| 3.10 | Arm durability test | 6.20 | 30 000 | 400 N | Pass |
| 3.11 | Foot rest durability test | 6.21 | 50 000 | 1000 N | N/A |
| 3.12 | Leg forward static load test | 6.15 | 10 | 500 N Seat: 1000 N | Pass |
| 3.13 | Leg sideways static load test | 6.16 | 10 | 400 N Seat: 1000 N | Pass |
| 3.14 | Seat impact test | 6.24 | 10x2 | 240 mm | Pass |
| 3.15 | Back impact test | 6.25 | 10 | 210 mm/38° | Pass |
| 3.16 | Arm impact test | 6.26 | 10 | 210 mm/38° | Pass |
| 3.17 | Auxiliary writing surface static load test | 6.14 | 10 | 300 N | N/A |
| 3.18 | Auxiliary writing surface durability test | 6.22 | 10 000 | 150 N | N/A |

Appendix 2

Test object

Test object/ID: Armchair/Plateau, 1-seater with armrest

Dimensions

Width: 1250 mm

Depth: 840 mm

Height: 730 mm

Seat height: 460 mm

Mass: 40 kg

Components

Frame/legs: Oval steel tube, 20x40 mm

Seat/armrest/backrest: Plywood, flexible foam, fabric

Sampling: The test object was selected by the customer

Date of arrival at 2021-06-09

RISE test laboratory:

Observed defects before testing: No defects

Appendix 3

Pictures



Figure 1



Figure 2

Appendix 3



Figure 3



Figure 4

Appendix 3



Figure 5



Figure 6

Verification

Transaction 09222115557465235807

Document

175885A Johanson Design Plateau 1-sits

Main document

8 pages

Initiated on 2022-03-17 13:38:48 CET (+0100) by Bengt-

Åke Andersson (BA)

Finalised on 2022-03-17 16:17:01 CET (+0100)

Signing parties

Bengt-Åke Andersson (BA)

RISE Research Institutes of Sweden AB

Company reg. no. 556464-6874

bengt-ake.andersson@ri.se




Signed 2022-03-17 13:39:16 CET (+0100)

Annika Ahagen (AA)

RISE Research Institutes of Sweden AB

Company reg. no. 556464-6874

annika.ahagen@ri.se



Signed 2022-03-17 16:17:01 CET (+0100)

This verification was issued by Scrive. Information in italics has been safely verified by Scrive. For more information/evidence about this document see the concealed attachments. Use a PDF-reader such as Adobe Reader that can show concealed attachments to view the attachments. Please observe that if the document is printed, the integrity of such printed copy cannot be verified as per the below and that a basic print-out lacks the contents of the concealed attachments. The digital signature (electronic seal) ensures that the integrity of this document, including the concealed attachments, can be proven mathematically and independently of Scrive. For your convenience Scrive also provides a service that enables you to automatically verify the document's integrity at: <https://scrive.com/verify>

