REPORT

Issued by an Accredited Testing Laboratory

Contact person
Annika Ahagen
Division Built Environment
+46 10 516 62 68
annika.ahagen@ri.se

Date	Reference	Page
2024-10-17	1286018A	1 (1)

Johanson Design AB
Anders Anderssons väg 7
285 35 MARKARYD
SWEDEN

Testing of seating furniture according to FprEN 16139:2024

(3 appendices)

1286018

Customer:	Johanson Design AB
Test object/ID:	Armchair/Milo Low 08
Test method:	FprEN 16139:2024 Furniture - Strength, durability and safety - Requirements for non-domestic seating. Test level 1
Scope:	Complete test
Date of test:	2024-09-23 – 2024-10-17
Test result:	The tested object passed the test
Reservation:	The test results in this report apply solely to the specimen tested
Test environment:	23 ± 2ºC and 50 ± 5% relative humidity
Measurement uncertainty:	Decision rule according to EN ISO IEC 17025:2018 clause 3.7 No account is taken of measurement uncertainty when reporting numerical results
Additional information:	The test method and results also comply with EN 16139:2013

RISE Research Institutes of Sweden AB

Department Building and Real Estate - Technical Wood Assessment

Performed by

Annika Ahagen

Examined by

Bengt-Åke Andersson

Appendices

1. Test result (3 pages)
2. Test object (1 page)
3. Pictures (2 pages)

This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Accred. No. 1002
Testing
ISO/IEC 17025

Transaktion 09222115557529888332 Signerat AA, BA

Appendix 1

Test result

Abbreviations: N/A = Not applicable
N/T = Not tested

Table 1

1.	Safety	FprEN 16139	Result
1.1	<u>General requirements</u> The seating shall be so designed as to minimise the risk of injury to the user. All accessible parts shall be so designed that physical injury and damage are avoided. This requirement is met when: a) accessible corners are rounded or chamfered; b) the edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded or chamfered; c) the edges of handles are rounded or chamfered in the direction of the force applied; d) all other edges are free from burrs and rounded or chamfered; e) the ends of hollow components are closed or capped. Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided. It shall not be possible for any load bearing part of the seating to come loose unintentionally. All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use	4.1 4.2	Pass
1.2	<u>Shear and squeeze points</u> With the exception of tipping seats there shall be no shear and squeeze points created by parts of the seating operated by powered mechanisms, e.g. springs and gas lifts. There shall be no shear and squeeze points created by forces applied during normal use as well as during normal movements and actions Note! Shear and squeeze points that are created only during manually setting up and folding are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain.	4.3	Pass

Transaktion 09222115557529888332 Signerat AA, BA

Appendix 1

Table 2

2.	Stability	EN 1022:2023	Result
2.1	Forwards overbalancing Requirement ≥ 20 N	7.3.1	Pass >100 N
2.2	Forwards overturning for seating with footrest	7.3.2	N/A
2.3	Corner stability test Requirement 30 kg	7.3.3	Pass
2.4	Sideways overbalancing, all seating without arms Requirement ≥ 20 N	7.3.4	N/A
2.5	Sideways overbalancing, all seating with arms Requirement ≥ 20 N	7.3.5.2	Pass >100 N
2.6	Sideways overbalancing, seating with raised side edges	7.3.5.3	N/A
2.7	Rearwards overbalancing, all seating with backs Requirement ≥ 198 N	7.3.6	Pass >250 N

Table 3

3.	Strength, durability	Reference EN 1728	Cycles	FprEN 16139 level 1	Result
3.1	Seat and back static load test	6.4	10	Seat: 1600 N Back: 560 N	Pass
3.2	Seat front edge static load test	6.5	10	1300 N	Pass
3.3	Vertical static load on back rests	6.6	10	600 N Seat: 1300 N	Pass
3.4.1	Foot rest static load test	6.8	10	1300 N	N/A
3.4.2	Leg rest static load test	6.9	10	1300 N	N/A
3.5	Arm sideways static load test	6.10	10	400 N	Pass
3.6	Arm downwards static load test	6.11	5	750 N	Pass
3.7.1	Vertical upwards static load on arm rests for seating which may be moved when occupied	6.13.1	10	1200 N	N/A
3.7.2	Vertical upwards static load on arm rests for stackable seating	6.13.2	10	25 kg	N/A

Transaktion 09222115557529888332 Signerat AA, BA

Appendix 1

3.	Strength, durability	Reference EN 1728	Cycles	FprEN 16139 level 1	Result
3.8	Seat and back durability test	6.17	100 000	Seat: 1000N Back: 300 N	Pass
3.9	Seat front edge durability test	6.18	50 000	800 N	Pass
3.10	Seat side-to-side durability test (For single column seat)	Annex D	10 000	1100 N	N/A
3.11	Arm durability test	6.20	30 000	400 N	Pass
3.12	Foot rest durability test	6.21	50 000	1000 N	N/A
3.13	Leg rest durability test	Annex H	10 000	1000 N	N/A
3.14	Leg forward static load test	6.15	10	500 N Seat: 1000 N	Pass
3.15	Leg sideways static load test	6.16	10	400 N Seat: 1000 N	Pass
3.16	Seat impact test	6.24	10 x 2	240 mm	Pass
3.17	Backward fall test	6.28	5	Unloaded	N/A
3.18	Back impact test	6.25	10	210 mm/38°	Pass
3.19	Arm impact test	6.26	10	210 mm/38°	Pass
3.20	Auxiliary writing surface static load test	6.14	10	300 N	N/A
3.21	Auxiliary writing surface durability test	6.22	10 000	150 N	N/A

Transaktion 09222115557529888332 Signerat AA, BA

Appendix 2

Test object

Test object/ID:	Armchair/Milo Low 08

Dimensions [1]

Width:	760 mm
Depth:	750 mm
Height:	800 mm
Seat height (in front):	420 mm
Mass:	13.5 kg

Components

Frame/legs:	Metal tube, Ø22 m Metal plate, 10 mm
Seat/Backrest/Armrest:	Fabric, flexible foam Metal rod Ø8 mm Ø14 mm, 5x30x230 mm

Sampling:	The test object was selected by the customer
Date of arrival at RISE test laboratory:	2024-08-22
Observed defects before testing:	No defects

[1] The dimensions are only intended to unambiguously identify the test object and do not claim to be metrologically accurate

Transaktion 09222115557529888332 Signerat AA, BA

Appendix 3

Pictures

Figure 1

Figure 2

Figure 3

Figure 4

Transaktion 09222115557529888332 Signerat AA, BA

Appendix 3

Figure 5

Figure 6

Transaktion 09222115557529888332 Signerat AA, BA

Verifikat

Transaktion 09222115557529888332

Dokument

1286018A Johanson Design Milo Low 08
Huvuddokument
7 sidor
Startades 2024-10-21 14:36:49 CEST (+0200) av Annika Ahagen (AA)
Färdigställt 2024-10-22 07:26:12 CEST (+0200)

Signerare

Annika Ahagen (AA)
RISE Research Institutes of Sweden AB
Org. nr 556464-6874
annika.ahagen@ri.se



Signerade 2024-10-22 07:26:12 CEST (+0200)

Bengt-Åke Andersson (BA)
RISE Research Institutes of Sweden AB
Org. nr 556464-6874
bengt-ake.andersson@ri.se

Signerade 2024-10-21 15:36:21 CEST (+0200)

Detta verifikat är utfärdat av Scrive. Information i kursiv stil är säkert verifierad av Scrive. Se de dolda bilagorna för mer information/bevis om detta dokument. Använd en PDF-läsare som t ex Adobe Reader som kan visa dolda bilagor för att se bilagorna. Observera att om dokumentet skrivs ut kan inte integriteten i papperskopian bevisas enligt nedan och att en vanlig papperutskrift saknar innehållet i de dolda bilagorna. Den digitala signaturen (elektroniska förseglingen) säkerställer att integriteten av detta dokument, inklusive de dolda bilagorna, kan bevisas matematiskt och oberoende av Scrive. För er bekvämlighet tillhandahåller Scrive även en tjänst för att kontrollera dokumentets integritet automatiskt på: https://scrive.com/verify